# ELONEX™
## Experiential

1534mm (Width)

901mm (Height)

73mm (Depth)
16.5mm (Ultra-Thin Aluminium Band)

WIFI / 3G READY
**ASPECT RATIO 16:09**
MAX RESOLUTION
ULTRA-HD 3840 x 2160
**45KG NET WEIGHT**
54KG GROSS WEIGHT
**115W POWER CONSUMPTION**
INPUT VOLTAGE:
AC110~240V(50Hz~60Hz)

# 65" 'ULTRA-HD' AD DISPLAYS
## USB & CLOUD NETWORK READY

| | |
|---|---|
| Manufacturer & Model | ELONEX AD652-4KNT-BBW1-V-V1 |
| Dual Control Android | Android 4.4.2 Dual Core 1GB/4GB with USB & SD Card connections, Wi-Fi & 3G Ready, On/Off Eco Timer & Screen Orientation, UI- Remote Control (no keyboard or mouse required) |
| Dual Control Video Board | Video Board HDMI, VGA, 3.5m Audio |
| Software | DSA StandBy Player USB Digital Signage Application & Playlist builder (for Mac and PC) Displays (JPEG / PNG) and vvideo (Mp4) |
| Cloud & Network Ready | Access to a range of Cloud Digital Signage Software. Upgrade to DSA StandBy Player Network Digital Signage Edition from QSSG (Quick Start Set up Guide) Instantly |
| Panel Size | Landscape 65 inch |
| Housing | Aluminum Band Tablet Style |
| Colour | Black and Silver Band |
| Colour Temperature | 10000K |

| | |
|---|---|
| Lifetime (hours) | 50,000 |
| Resolution of PCB | 480P/720P/1080/3840P |
| Display colour | 16.7M |
| Brightness | 450cd/m2 |
| Contrast | 5000:1 |
| Viewing angle | 178°/178° |
| Response time | 5ms |
| Vessa (Hanging) | 400 x 400 |
| Audio | 5W, 8Ω Audio Socket (3.5mm) |
| Working Temperature | 0 °C to 50 °C |
| Accessories | Remote Control, On Screen User Manual, Rear Wall Breacket & Hanging VESA 100. QSSG (Quick Start Set up Guide) warranty software registration plus upgrade feature. |